

Technical Product Datasheet

HadleySFS Slotted 'U' Track 100mm

HadleySFS Slotted 'U' Tracks are cold-rolled steel Tracks used at the head of HadleySFS systems to provide a +/-20mm deflection detail for non-loadbearing external walls.

Manufactured in accordance with EN 1090-1:2009

Manufactured from steel grade S450GD+Z275 to EN 10346:2015









Scan QR code for Hadley System *Golden Thread*Documents: Technical Datasheet, Material Safety
Datasheet, Declaration of Performance (DoP), O&M
Manual and more...



Product Information



SYSTEM PERFORMANCE INFORMATION:

To be installed as a part of a complete Hadley system to achieve both Fire and Acoustic performance. To understand more about our fully warranted and tested solutions, please contact our Hadley Construction Technology Team.

SYSTEMS USED:

SFS Infill SFS High-Bay Walling

SFS-HAD-XX-ZZ-TE-X-120

Rev	Date	Comment	Ву	Chk	Арр
1.0	12/09/2025	First Issue	IF	FM	JS

Item code	Web	Flange	Gauge	Weight
	(mm)	(mm)	(mm)	(kg/m)
104TS7018	104	70	1.8	3.39

Sold at a fix 3m length.

STORAGE & HANDLING:

When installing Hadley components please ensure full PPE is used and the site is practicing a safe working environment alongside industry standards.

DISPOSAL:

Hadley Metal is fully recyclable.